

## Proware announces Fibre-to-IDE RAID subsystem 2U chassis with eight hot swappable drives

June 2003 Taipei, Proware Technology Corp. is pleased to announce its newly innovated Fibre-to-IDE RAID subsystem – the Simbolo SB-2803FO. The Simbolo SB-2803FO is a superior data storage option for mission critical and high performance application.

This industry standard 19-inch rack-mountable 2U chassis RAID subsystem features 8 hot-swappable Ultra DMA drive trays. For mission critical applications requiring aggressive performance, total reliability and system scalability, the SB-2803FO is the obvious solution.



- Supports RAID levels 0, 1, 0+1, 3 and 5.
- Features an Intel i80303 64-bit RISC I/O processor.
- Supports up to 512MB of cache.
- Smart-function LCD display.
- High quality advanced cooling fans.
- Environmental monitoring unit.
- 2Gb/s FC-AL (Fibre Channel Arbitrated Loop) host port, dual loop optical SFP LC (short wave).
- Supports up to eight (8) 1" hot-swappable Ultra DMA hard drives.
- Redundant 300W load-sharing hot-swappable power supplies.
- Supports hot spare and automatic hot rebuild.
- Industry standard 19" rack-mountable 2U chassis.
- Transparent data protection for all popular operating systems.
- Tagged command queuing for 255 commands, allows for overlapping data streams.
- Allows online capacity expansion within the enclosure.
- Dual host channels support clustering technology.
- Built-in serial port interface for remote event notification.
- Real time drive activity and status indicators.
- Local audible event notification alarm.
- Browser-based Java GUI management utility.