

Proware announces 2Gb FC-to-SATA RAID subsystem

2Gb FC-to-SATA RAID subsystem

July 2004 Taipei, Proware Technology Corp. is pleased to announce its newly innovated 2Gb FC-to-SATA RAID subsystem – the Simbolo SB-2128FA & 2808FA.



- Supports RAID levels 0, 1, 0+1, 3, 5, 30, 50 and JBOD
- Features an Intel 80321 64-bit RISC I/O processor
- Supports up to 1024MB of cache
- Smart-function LCD display
- High quality advanced cooling fans
- Environmental monitoring unit
- Dual Loop FC-AL (2 Gb/s) host port
- Array roaming
- E-mail notification
- Supports up to twelve (SB-2128FA) / eight (SB-2808FA) 1" hot-swappable S-ATA hard drives
- Redundant 350W (SB-2128FA) / 300W (SB-2808FA) hot-swappable power supplies w/PFC

- Supports hot spare and automatic hot rebuild
- Industry standard 19" rack-mountable 2U chassis
- Transparent data protection for all popular operating systems
- Tagged command queuing for 256 commands, allows for overlapping data streams
- Allows online capacity expansion within the enclosure
- Dual host channels support clustering technology
- Built-in serial port interface for remote event notification
- Real time drive activity and status indicators
- Local audible event notification alarm
- Browser-based Java GUI management utility
- Supports R-Link connectivity (SB-2128FAT / SB-2808FAT)