EPICA EN-1400 6Gb SATA NAS EN-1400A6B-CM



As the number of users and the amount of data grows, how to find a storage which can offer complete data protection, good performance, with reliability and high scalability is the key for all enterprises and companies.

The EN-1400 6G SATA NAS based on latest proNAS 3.6 operating system. Except for basic NAS functions, it supports a variety of advanced storage management and application features such as VAAI, Thin-Provisioning, etc, and it can be deployed easily in any IT environment since it supports multiple interfaces for different host server and clients.

For data protection, EN-1400 supports RAID level 0, 1, 5, 6, 10 and Linear(JBOD) mode, and drives can be set hot spares, have automatically hot rebuilding and online capacity expansion within the enclosure. EN-1400 has a fully-featured backup solution including manual or scheduled backup for file, folder, and shares, and it can be backup and restore from multiple local or remote devices. And there are volume clone, snapshot, remote replication, and data copy for options, which are all designed to ensure and enhance your precious data.

Features

- Account Manager support NIS
- Allows online capacity expansion within the enclosure
- Backup to Cloud (Amazon S3)
- Backup/Restore from attached storage (USB/eSATA/iSCSI/RDX/USM)
- Backup/Restore from remote share (CIFS/NFS)
- Bonjour Protocol, easily connect to NAS
- Compression (Support on ZFS file system)
- Central data and storage management
- Data backup via backup plan/schedule
- Data copy (1:1)
- Deduplication (Support on ZFS file system)
- EXT4 support extend over 16TB
- iSCSI/share volume replication
- ISO mount
- Latest volume snapshot technology
- Local and external account management, support large account import

- Online expansion file system
- Plug-in management
- Select share or file for backup/restore
- Share management and permission
- (support ACL setting)
- Support Internet Gateway
- Support iSCSI target for IP SAN
- Support iSCSI initiator
- Support iSCSI multi host
- Support e-mail notification, SNMP Trap/MIB and system log
- System configuration backup/restore
- Thin Provisioning
- Volume Clone (EXT3/EXT4/XFS/NTFS/VMFS/ ZFS/Btrfs)
- Volume replication to enhance data protection
- VMware ESXi 5 iSCSI/NFS VAAI support
- Wizard-oriented GUI design
- WORM (Write Once Read Many) support CIFS/NFS



Series Technical Specifications

EN-1400A6B-CM

NAS Hardware Specification

| Intel Celeron 3.4GHz or above | Support drive hot spare and automatic hot rebuild |
|--|---|
| Optional: Intel Pentium, Core i3 / i5 / i7 | Locally audible event notification alarm |
| Cache memory : 8GB DDR4 SDRAM up to 32GB | Power requirements |
| Four USB3.0 ports | AC 100V ~ 240V Full range |
| Two Gigabit Ethernet ports | 6A~3A, 60~50Hz |
| Support RAID level: RAID 0, 1, 5, 6, 10 and Linear(JBOD) | Environmental |
| Up to Four (4) 2.5"/3.5" hot-swappable 6Gb/s SATA3 hard drives | Relative humidity : 10%~85% Non-condensing |
| Real-time drive activity and status indicators | Operating temp : 10°C~40°C(50°F~104°F) |
| Environmental monitoring unit | Physical Dimension: 44(H) x 446.4(W) x 500(D)mm |
| 250W power supply with PFC | Weight: 7.8kg (without drives) |
| | toight florg (white a troop) |
| NAS Functionality | |
| Storage Management | Microsoft Active Directory Authentication (ADS) |
| Volume management (Support Btrfs, ZFS, XFS, EXT3 and EXT4 file | Network Information Service (NIS) |
| system) | Support OpenLDAP service |
| Support Compression and Deduplication (Support on ZFS file | Support creating users by batch |
| system) | User quota management |
| Disk usage statistics | Share level security |
| Hot spare drives | File level security |
| SCSI Target manager: Support LUN Mapping/Initiator Filter/Thin | User ID security for NFS |
| Provisioning | Recycle bin (Samba) |
| VAAI support for iSCSI/NFS | File access log, audit (Samba) |
| General | Write Once Read Many (WORM) |
| ndependent file server | Block Storage |
| Multiple language support | iSCSI Target Support |
| Support UPS | Thin Provisioning support |
| Support LV encryption | VMware VAAI support |
| System Management | Virtualization |
| Automatic IP address configuration | VMware/Citrix/Hyper-V |
| Web browser-based management | VMware VAAI for NFS support |
| SNMP management and notification | Attached Storage |
| Fail-free online firmware upgrade | ISO Mount |
| Unicode support | USB/eSATA/iSCSI initiator |
| Multi-node management GUI | Data Backup / Restore |
| System configuration backup/restore | Volume Clone (EXT3/EXT4/XFS/NTFS/VMFS/ZFS/Btrfs) |
| Central management | Symantec BackupExec Agent (by additional installation) |
| Quick wizard | Scheduling multi-snapshot (Support iSCSI snapshot) |
| Networking | Replication (Remote realtime data mirroring) |
| Support NIC/Trunking/Load Balance/Fail Over/802.3ad | Scheduling Rsync Replication |
| DHCP Server/DHCP Client | Support NetVault backup client (by additional installation) |
| WINS Server | Support CA ARCserve (by additional installation) |
| nternet gateway | Data copy (copy files to other share/attached storage) |
| DDNS | Scheduling backup |
| Protocols | Differential/incremental backup |
| TCP/IP, SMB/CIFS, NFS, SNMP, FTP/SFTP/FXP, HTTP, HTTPS, | iSCSI Replication |
| Telnet, SSH, AFP, WebDAV, Bonjour, TFTP | Amazon S3 backup |
| Client Operating Systems Support | backup/restore from attached storage |
| Microsoft® Windows® 98/ME/NT/2000/XP/2003/Vista/2008/Win7/ | (USB/eSATA/iSCSI/RDX*/USM*) |
| Windows 2012/Win 8/Win 10/2016 | Support Apple Time Machine |
| Jnix/Linux | Plug-in management |
| Mac OS | Anti-Virus |
| Authentication | Central management |
| _ocal user account/group | iTunes Server |
| | |

* By OEM request.

Specification are subject to change without notice. All company and product names are trademarks of their respective owners.

UNIFOSA CORP. Tel:886-2-2914-8001(Rep.) Fax:886-2-2914-7975 http://www.proware.com.tw E-mail:info@proware.com.tw

Your Storage Solutions Partner