

# EPICa

## EP - 2123-S6S6

2U 6Gb SAS – 6Gb SAS RAID Subsystem



The EP-2123-S6S6 RAID subsystem features 6Gb SAS host performance to increase system efficiency and performance. It features high capacity expansion, with 12 hot-swappable SAS2/SATA3 hard disk drive bays in a 19-inch 2U rackmount unit, scaling to a maximum storage capacity in the terabyte range.

### EXCEPTIONAL MANAGEABILITY

- The firmware-embedded Web Browser-based RAID manager allows local or remote management and configuration
- The firmware-embedded SMTP manager monitors all system events and user notification automatically
- The firmware-embedded SNMP agent allows remote to monitor events via LAN with no SNMP agent required
- Menu-driven front panel display
- Innovative modular architecture

### FEATURES

- Supports RAID levels 0, 1, 10(1E), 3, 5, 6, 30, 50, 60 and JBOD
- Supports online array roaming
- Online RAID level/stripe size migration
- Online capacity expansion and RAID level migration simultaneously
- Support global and dedicated hot spare
- Online volume set expansion
- Support multiple array enclosures per host connection
- Greater than 2TB per volume set (64-bit LBA support)
- Greater than 2TB per disk drive
- Supports 4K bytes/sector for Windows up to 16TB per volume set
- Disk scrubbing/ array verify scheduling for automatic repair of all configured RAID sets
- Login record in the event log with IP address and service (http, telnet and serial)
- Support intelligent power management to save energy and extend service life
- Support NTP protocol to synchronize RAID controller clock over the on-board LAN port
- Max 128 LUNs (volume set) per controller
- Transparent data protection for all popular operating systems
- Instant availability and background initialization
- Supports S.M.A.R.T, NCQ and OOB Staggered Spin-up capable drives
- Supports hot spare and automatic hot rebuild
- Local audible event notification alarm
- Redundant flash image for high availability
- Real time clock support



# Series Technical Specifications

<b>Model</b>	<b>EP-2123-S6S6</b>
<b>RAID Controller</b>	6Gb SAS – 6Gb SAS
<b>Host Interface</b>	Two 6Gb/s SAS (SFF-8088)
<b>Disk Interface</b>	6Gb/s SAS, 6Gb/s SATA
<b>SAS expansion</b>	One 6Gb/s SAS (SFF-8088)
<b>Capacity</b>	
- Direct attached	12 Disks
- Expansion	Up to 96 Disks
<b>Processor type</b>	800MHz RAID-On-Chip storage processor
<b>Cache memory</b>	1GB ~ 4GB DDR2-800 ECC Registered SDRAM
<b>Battery backup</b>	Optional
<b>Management port support</b>	Yes
<b>RAID Features</b>	
<b>RAID level</b>	0, 1, 10(1E), 3, 5, 6, 30, 50, 60 and JBOD
<b>Array group</b>	Up to 128
<b>LUNs</b>	Up to 128
<b>Hot spare</b>	Yes
<b>Drive roaming</b>	Yes
<b>Online rebuild</b>	Yes
<b>Variable stripe size</b>	Yes
<b>E-mail notification</b>	Yes
<b>Online capacity expansion, RAID level /stripe size migration</b>	Yes
<b>Online array roaming</b>	Yes
<b>Online consistency check</b>	Yes
<b>SMTTP manager and SNMP agent</b>	Yes
<b>Redundant flash image</b>	Yes
<b>Instant availability and background initialization</b>	Yes
<b>S.M.A.R.T. support</b>	Yes
<b>MAID 2.0</b>	Yes
<b>Bad block auto-remapping</b>	Yes
<b>Enclosure</b>	
<b>Platform</b>	Rackmount
<b>Form factor</b>	2U
<b># of hot swap trays</b>	12
<b>Tray lock</b>	Yes
<b>Disk status indicator</b>	Access / Fail LED
<b>Backplane</b>	SAS2 / SATA3 Single BP
<b># of PS/Fan modules</b>	400W x 2 w/PFC
<b># of fans</b>	2
<b>Power requirements</b>	AC 90V ~ 264V Full range 7.5A ~ 4A, 47Hz ~ 63Hz
<b>Environmental</b>	
<b>Relative humidity</b>	10% ~ 85% Non-condensing
<b>Operating temperature</b>	10°C ~ 40°C (50°F ~ 104°F)
<b>Physical dimension</b>	590(L) x 482 (W) x 88(H) mm
<b>Weight (Without disk)</b>	18.2 Kg

*Specification is subject to change without notice.*

*All company and product names are trademarks of their respective owners.*



UNIFOSA CORP.  
Tel:886-2-2914-8001(Rep.) Fax:886-2-2914-7975  
<http://www.proware.com.tw> E-mail:[info@proware.com.tw](mailto:info@proware.com.tw)

**Your Storage Solutions Partner**