

EPICa

EP - 2123J-S6S6

EP - 2123JD-S6S6

2U 12Bays 6G SAS2.0 JBOD Enclosure Solution



The EPICa EP-2123J/JD-S6S6 is a 19-inch 2U 12 bays rackmount JBOD unit. It features the latest SAS2 (6Gb/s) interface and designed to fit in with the environments which needed highly reliable and relentless data growth. The EP-2123J/JD-S6S6 is also a versatile SAS2 / SATA3 Disk Expansion system, ideal for high capacity and scalability storage in IT demands. Based on the 6G SAS2.0 technology, the EP-2123J/JD-S6S6 supporting the choice of SAS2 and SATA3 drive configurations to deliver the best cost-performance index with higher bandwidth.

Features

- 12 hot-swappable drive bays in a rackmount 2U chassis
- Simultaneously support SAS2 or SATA3 disk
- Single or dual SAS2 JBOD controller module
- Each SAS2 JBOD controller module consist of three mini SAS (4X) port
- Power Supply and cooling system contained in 1 module for efficient cooling
- Two 400W redundant hot swappable power supplies
- Incorporates a cableless design for maximum signal integrity
- Utilizes industry-standard SCSI Enclosure Services to monitor enclosure and disk environmental conditions

Enclosure monitoring

- S.E.S. support for standard enclosure management
- System LED indications
- Fan speed monitoring
- Power supply monitoring
- System voltage monitoring
- System temperature monitoring
- System alarm



Series Technical Specifications

EP-2123J-S6S6/EP-2123JD-S6S6

RAID Controller	JBOD
Controller	Single / Redundant
Host Interface	One / Two 4x mini SAS (6Gb/s)
Disk Interface	SAS/SAS2 (3Gb/6Gb) or SATA2/3(3Gb/6Gb) *
SAS expansion	Two / Four 4x mini SAS (6Gb/s)
Capacity	
- Direct Attached	12 Disks
- Expansion	Refers to controller specification
Monitor Port Support	Yes
Enclosure	
Platform	Rackmount
Form Factor	2U
# of Hot Swap Trays	12
Tray Lock	Yes
Disk Status Indicator	Access / Fail LED
Backplane	SAS / SATA Single BP
# of PS / Fan Modules	400W x 2 w/PFC
# of Fans	2
Power Requirements	AC 90V ~ 264V Full Range, 8A ~ 4A, 47Hz ~ 63Hz
Environmental	
Relative Humidity	10% ~ 85% Non-condensing
Operating Temperature	10°C ~ 40°C (50°F ~ 104°F)
Physical Dimension	590(L) x 482 (W) x 88(H) mm
Weight	18.2 / 19.7 Kg (Without Disk)

Specification is subject to change without notice.

All company and product names are trademarks of their respective

* Request optional dongle board for SATA2/3 hard drive.



UNIFOSA CORP.

Tel:886-2-2914-8001(Rep.) Fax:886-2-2914-7975

<http://www.proware.com.tw> E-mail:info@proware.com.tw

Your Storage Solutions Partner