

EPICa

EP - 4423S1/D1-S6S6

EP - 4423S1/D1-F8S6

4U 6Gb SAS – 6Gb SAS / 8Gb FC – 6Gb SAS
Redundant RAID Subsystem



The EP-4423 series RAID subsystem features 6Gb SAS or 8Gb FC-AL host performance to increase system efficiency and performance. It features high capacity expansion, with 42 hot-swappable SAS2/SATA3 hard disk drive bays in a 19-inch 4U rackmount unit, scaling to a maximum storage capacity in the terabyte range. The EP-4423D1 series also supports dual controllers which provide better fault tolerance and higher reliability of system operation.

Exceptional Manageability

- The firmware-embedded Web Browser-based RAID manager allows local or remote management and configuration
- The firmware-embedded SMTP manager monitors all system events and user notification automatically
- The firmware-embedded SNMP agent allows remote to monitor events via LAN with no SNMP agent required
- Menu-driven front panel display
- Innovative Modular architecture

Feature

- Supports RAID levels 0, 1, 10(1E), 3, 5, 6, 30, 50, 60 and JBOD
- Supports online Array roaming
- Online RAID level/stripe size migration
- Online capacity expansion and RAID level migration simultaneously
- Support global and dedicated hot spare
- Online Volume Set Expansion
- Support multiple array enclosures per host connection
- Greater than 2TB per volume set (64-bit LBA support)
- Greater than 2TB per disk drive
- Supports 4K bytes/sector for Windows up to 16TB per volume set
- Disk scrubbing/ array verify scheduling for automatic repair of all configured RAID sets
- Login record in the event log with IP address and service (http, telnet and serial)
- Support intelligent power management to save energy and extend service life
- Support NTP protocol to synchronize RAID controller clock over the on-board LAN port
- Max 128 LUNs (volume set) per controller
- Transparent data protection for all popular operating systems
- Instant availability and background initialization
- Multi-path & load-balancing support (Microsoft MPIO)
- Automatic synchronization of firmware version in the dual-active mode
- Supports S.M.A.R.T, NCQ and OOB Staggered Spin-up capable drives
- Supports hot spare and automatic hot rebuild
- Local audible event notification alarm
- Redundant flash image for high availability
- Real time clock support



Series Technical Specifications

| Model | EP-4423S1/D1-S6S6 | EP-4423S1/D1-F8S6 |
|--|---|---|
| RAID Controller | 6Gb SAS – 6Gb SAS | 8Gb FC – 6Gb SAS |
| Controller | Single or Redundant | Single or Redundant |
| Host Interface | Two / Four 6Gb/s SAS (SFF-8088) | Four / Eight FC-AL (8 Gb/s) |
| Disk Interface | 6Gb/s SAS, 6Gb/s SATA | 6Gb/s SAS, 6Gb/s SATA |
| SAS Expansion | One / Two 6Gb/s SAS (SFF-8088) | One / Two 6Gb/s SAS (SFF-8088) |
| Capacity | | |
| - Direct Attached | 42 Disks | 42 Disks |
| - Expansion | Up to 252 Disks | Up to 252 Disks |
| Processor Type | 800MHz Dual Core RAID-On-Chip processor | 800MHz Dual Core RAID-On-Chip processor |
| Cache Memory | 1GB ~ 8GB / 2GB ~ 16GB DDR3-1333 ECC SDRAM | 1GB ~ 8GB / 2GB ~ 16GB DDR3-1333 ECC SDRAM |
| Battery Backup | Optional | Optional |
| Management Port Support | Yes | Yes |
| RAID Features | | |
| RAID level | 0, 1,10(1E), 3, 5, 6, 30, 50, 60 and JBOD | 0, 1,10(1E), 3, 5, 6, 30, 50, 60 and JBOD |
| Array Group | Up to 128 | Up to 128 |
| LUNs | Up to 128 | Up to 128 |
| Hot Spare | Yes | Yes |
| Drive Roaming | Yes | Yes |
| Online Rebuild | Yes | Yes |
| Variable Stripe Size | Yes | Yes |
| E-mail Notification | Yes | Yes |
| Online capacity expansion, RAID level / stripe size migration | Yes | Yes |
| Online Array Roaming | Yes | Yes |
| Online consistency check | Yes | Yes |
| SMTMP manager and SNMP agent | Yes | Yes |
| Redundant Flash image | Yes | Yes |
| Instant availability and background initialization | Yes | Yes |
| S.M.A.R.T. support | Yes | Yes |
| MAID 2.0 | Yes | Yes |
| Bad block auto-remapping | Yes | Yes |
| Enclosure | | |
| Platform | Rackmount | Rackmount |
| Form Factor | 4U | 4U |
| # of Hot Swap Trays | 42 | 42 |
| Tray Lock | Yes | Yes |
| Disk Status Indicator | Access / Fail LED | Access / Fail LED |
| Backplane | SAS2 / SATA3 | SAS2 / SATA3 |
| # of PS / Fan Modules | 1100W x 2 w/PFC | 1100W x 2 w/PFC |
| # of Fans | 11 | 11 |
| Power Requirements | AC 90V ~ 254V Full Range, 50Hz~60Hz | AC 90V ~ 254V Full Range, 50Hz~60Hz |
| Environmental | | |
| Relative Humidity | 10% ~ 85% Non-condensing | 10% ~ 85% Non-condensing |
| Operating Temperature | 10°C ~ 40°C (50°F ~ 104°F) | 10°C ~ 40°C (50°F ~ 104°F) |
| Physical Dimension | 810(L) x 482.6(W) x 176(H) mm | 810(L) x 482.6(W) x 176(H) mm |
| Weight (Without Disk) | 48.5 / 50 Kg | 48.5 / 50 Kg |

Specification is subject to change without notice.

All company and product names are trademarks of their respective owners.



UNIFOSA CORP.
Tel:886-2-2914-8001(Rep.) Fax:886-2-2914-7975
<http://www.proware.com.tw> E-mail:info@proware.com.tw

Your Storage Solutions Partner